

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A lead assembly comprising:
 - a lead body extending from a distal end to a proximal end;
 - a conductor disposed within the lead body;
 - a piston movably disposed within the lead body and having an outer surface including a recess;
 - a fixation helix mechanically supported by the piston at a first portion of the fixation helix, ~~wherein the first portion of the fixation helix supported by the piston and having one or more helical drive grooves forming~~ forms a drive mechanism that advances the fixation helix and ~~the helical drive grooves positioned on an outer surface of the piston in which includes~~ successive turns of the fixation helix that are partially recessed within the recess of the piston with a portion of the fixation helix above ~~an~~ the outer surface of the piston; and
 - a housing portion positioned near the distal end of the lead body, the housing portion including a guide disposed on an inner surface thereof in which the first portion of the fixation helix rides along during at least one of advancing or retracting of the fixation helix relative to the lead body.
2. (Original) The lead assembly as recited in claim 1, wherein the first portion of the fixation helix is coupled with the piston.
3. (Previously Presented) The lead assembly as recited in claim 1, wherein the piston has the recess wrapped around, and extending inwardly from, the outer surface thereof such that one or more portions of the recess are separated from one another by a non-recessed portion, and at least a portion of the first portion of the fixation helix is disposed within the recess.
4. (Previously Presented) The lead assembly as recited in claim 1, wherein the recess has a helical shape.

5. (Previously Presented) The lead assembly as recited in claim 1, wherein the recess has a first width and the first width is less than a wire diameter of the first portion of the fixation helix.

6. (Previously Presented) The lead assembly as recited in claim 3, wherein approximately 1/3 to 1/2 of a wire diameter of the fixation helix is disposed within the recess.

7. (Canceled)

8. (Currently Amended) A lead assembly comprising:

a lead body extending from a distal end to a proximal end;

a housing positioned near the distal end of the lead body, the housing including a guide disposed on an inner surface thereof;

a conductor disposed within the lead body;

a piston movably disposed within the housing and having an outer surface including a recess; and

a fixation helix coupled with, and protruding radially around, the piston along a first longitudinal portion of the fixation helix, wherein the first portion of the fixation helix is coupled with ~~the piston forming helical drive grooves positioned on an outer surface of~~ and mechanically supported by the piston ~~in which~~ and successive turns of the fixation helix are partially recessed within the recess of the piston with a portion of the fixation helix above ~~an~~ the outer surface of the piston;

wherein the fixation helix forms a drive mechanism that rides along the guide allowing at least one of advancing or retracting of the fixation helix relative to the lead body.

9. (Previously Presented) The lead assembly as recited in claim 8, wherein the guide is a helical guide protruding from the inner surface of the housing.

10. (Previously Presented) The lead assembly as recited in claim 9, wherein the helical guide is a segmented helical guide.

11. (Previously Presented) The lead assembly as recited in claim 8, wherein the fixation helix is coupled with the piston along the recess extending inward from an outer surface of the piston,

a first portion of the recess separated from a second portion of the recess by a non-recessed piston portion.

12. (Canceled)

13. (Original) The lead assembly as recited in claim 8, wherein the fixation helix is coupled with the piston along a helical recess within the piston.

14. (Original) The lead assembly as recited in claim 8, wherein the fixation helix is electrically coupled with the conductor.

15. (Currently Amended) A lead assembly comprising:

a conductor;

a piston electrically coupled with the conductor and having an outer surface including a recess;

an active fixation helix mechanically supported by the piston at a first portion of the fixation helix, wherein the first portion of the fixation helix ~~supported by the piston and having one or more helical drive grooves forming~~ forms a drive mechanism that longitudinally advances and retracts the fixation helix, the ~~helical drive grooves~~ fixation helix being positioned on ~~an~~ the outer surface of the piston ~~in which, wherein~~ successive turns of the fixation helix are partially recessed within the recess of the piston with a portion of the fixation helix above an outer surface of the piston; and

a housing including a guide therein, the guide extending from an inner surface of the housing and adapted to interact directly with the first portion of the fixation helix.

16. (Original) The lead assembly as recited in claim 15, wherein the active fixation helix is electrically coupled with the piston.

17. (Previously Presented) The lead assembly as recited in claim 15, wherein the active fixation helix is recessed within an outer axial surface portion of the piston.

18. (Currently amended) The lead assembly as recited in claim 15, further comprising ~~one or more~~ than one recess in the piston, the recesses being recessed groove portions separated by non-

recessed groove portions, wherein the active fixation helix is mechanically coupled with the piston via the one or more of the ~~recesses~~ recessed groove portions.

19. (Currently Amended) A method comprising:

providing a lead assembly including:

a lead body extending from a distal end to a proximal end;

a conductor disposed within the lead body;

a piston movably disposed within the lead body and having an outer surface including a recess;

a fixation helix mechanically supported by, and protruding radially around, the piston at a first portion of the fixation helix, wherein the first portion of the fixation helix ~~having one or more helical drive grooves forming forms a drive mechanism, the helical drive grooves and is~~ positioned on ~~an~~ the outer surface of the piston ~~in which, and wherein~~ successive turns of the fixation helix are partially recessed within the recess of the piston with a portion of the fixation helix above ~~an~~ the outer surface of the piston;

a housing including a guide extending from an inner surface thereof;

rotating the fixation helix; and

longitudinally driving the fixation helix with the drive mechanism, including moving the first portion of the fixation helix directly along the guide.

20. (Previously Presented) The method as recited in claim 19, further comprising recessing at least a part of the first portion of the fixation helix within the piston such that a non-recessed portion of the piston separates successive turns of the fixation helix.

21. (Previously Presented) The method as recited in claim 19, further comprising recessing approximately 1/3 to 1/2 of a wire diameter of the fixation helix within the piston such that successive turns of the fixation helix are separated by a non-recessed piston portion.

22. (Original) The method as recited in claim 19, further comprising recessing at least a part of the first portion of the fixation helix within a helical groove of the piston.

23. (Original) The method as recited in claim 19, further comprising coupling the first portion of the fixation helix with the piston.

24. (Previously Presented) The lead assembly as recited in claim 1, wherein the housing portion comprises a molded component.

25. (Previously Presented) The lead assembly as recited in claim 8, further comprising a stop adapted to prevent over extension of the fixation helix from the lead body, the stop protruding around a portion of the piston.

26. (Previously Presented) The lead assembly as recited in claim 15, further comprising a fluoromarker coupled with a portion of the housing.